



Storage Tanks

- Permanent watertight storage
 - Up to 10.8 psi rating
 - Unlimited size range – 10,000 to 1,000,000+ gallons

For more information,
please contact your local
Contech Sales Representative at

800-338-1122

or visit

www.ContechES.com

Combined Sewer Overflow

Combined sewer overflow (CSO)/ Sanitary sewer overflow (SSO) discharged during heavy rain events are known to cause serious water pollution problems. Many communities are turning towards solutions such as CSO/SSO detention or storage.



Glycol

Airport deicing operations are generally equipped with storage for glycol and are configured to prevent used glycol from flowing into stormwater runoff. Contech's SRPE storage tanks provide leakproof storage of pure glycol, and can also be utilized to capture and store glycol runoff.



Detention

Detention systems are employed on a site to reduce the quantity of stormwater runoff leaving a site by temporarily storing the runoff that exceeds a site's allowable discharge rate, and releasing it slowly over time.



Rainwater Harvesting

Rainwater harvesting is an important tool to help meet stormwater runoff reduction requirements. Contech's DuroMaxx® Rainwater Harvesting System has all the components necessary to build an effective water re-use or runoff reduction practice.



DuroMaxx® SRPE Tank Sizes

Contech offers a variety of standard cistern sizes designed to accommodate a variety of storage requirements. Cistern storage volumes range from 2,000 – 22,500 gallons, and multiple cisterns can be connected using a small diameter manifold. Custom cistern sizes are also available.

Nominal Volume (gal)	Nominal Diameter (in)	Length (ft)	Pick Weight (lb)	Total Volume (gal)
2,000	60	16	1,250	2,280
3,000		24	1,750	3,420
4,500		32	2,000	4,560
6,500		48	2,750	6,840
2,500	66	16	1,500	2,760
4,000		24	2,000	4,135
5,250		32	2,500	5,515
8,000		48	3,500	8,270
3,000	72	16	1,750	3,281
4,500		24	2,250	4,922
6,500		32	2,750	6,563
9,500		48	4,000	9,844
3,500	78	16	2,000	3,579
5,000		24	2,500	5,368
7,000		32	3,000	7,158
10,500		48	4,250	10,737
4,000	84	16	2,250	4,465
6,500		24	2,750	6,697
8,500		32	3,250	8,929
13,000		48	4,500	13,394
5,500	96	16	2,500	5,830
8,500		24	3,250	8,744
11,500		32	4,000	11,659
17,000		48	5,250	17,489
14,000	108	30	4,250	14,277
19,000		40	5,250	19,036
16,500	120	29	4,750	16,503
20,000		36	5,500	20,486
22,500		40	6,000	22,762

* Custom tank sizes available. Please contact your local Contech representative..